

# TEXAS COMMISSION ON ENVIRONMENTAL QUALITY LEAD/COPPER SAMPLE SITE SELECTION POOL AND MATERIALS SURVEY FORM 20467

PWS ID:	SYSTEM TYPE:	☐ CWS ☐ NTNC	
SYSTEM NAME	: POPULATION:	☐ >100,000	
ADDRESS:		☐ 10,001 to 100,000	
CONTACT PER	SON:	3,301 to 10,000	
PHONE NUMBE	ER:	☐ 501 to 3,300	
EMAIL ADDRES	SS:	☐ 101 to 500	
		≤ 100	
ier site. The S	If it is not known whether lead is present in the plumbing, the DWA lead ban requiring the use of "lead-free" plumbing for a tructed after this date would not legally contain lead solder.		
ier site. The S	DWA lead ban requiring the use of "lead-free" plumbing for o		
ier site. The Souildings cons	DWA lead ban requiring the use of "lead-free" plumbing for o		
ier site. The S puildings cons	DWA lead ban requiring the use of "lead-free" plumbing for of tructed after this date would not legally contain lead solder.  For Community Water Systems (CWS), it is single family structure that contains lead pipes or copper pipes with lead solder and/or is served by lead service lines installed after 1982.  For Non-Transient Non-Community Systems (NTNCWS), it is buildings that contain copper pipes with lead solder installed after 1982 and/or served by lead service lines.	# of Sites	
ier site. The S	DWA lead ban requiring the use of "lead-free" plumbing for of tructed after this date would not legally contain lead solder.  For Community Water Systems (CWS), it is single family structure that contains lead pipes or copper pipes with lead solder and/or is served by lead service lines installed after 1982.  For Non-Transient Non-Community Systems (NTNCWS), it is buildings that contain copper pipes with lead solder	# of Sites	
ier site. The S puildings cons	Power lead ban requiring the use of "lead-free" plumbing for contructed after this date would not legally contain lead solder.  For Community Water Systems (CWS), it is single family structure that contains lead pipes or copper pipes with lead solder and/or is served by lead service lines installed after 1982.  For Non-Transient Non-Community Systems (NTNCWS), it is buildings that contain copper pipes with lead solder installed after 1982 and/or served by lead service lines.  For CWS, it is a building or multiple-family residences that contain lead pipes or copper pipes with lead solder installed after 1982, and/or is served by lead service lines.  For NTNCWS, it is buildings that contain copper pipes with lead solder installed before 1983.	# of Sites	
ier site. The S puildings cons TIER 1	DWA lead ban requiring the use of "lead-free" plumbing for of tructed after this date would not legally contain lead solder.  For Community Water Systems (CWS), it is single family structure that contains lead pipes or copper pipes with lead solder and/or is served by lead service lines installed after 1982.  For Non-Transient Non-Community Systems (NTNCWS), it is buildings that contain copper pipes with lead solder installed after 1982 and/or served by lead service lines.  For CWS, it is a building or multiple-family residences that contain lead pipes or copper pipes with lead solder installed after 1982, and/or is served by lead service lines.  For NTNCWS, it is buildings that contain copper pipes with	# of Sites  # of Sites  # of Sites	
ier site. The S puildings cons	Power lead ban requiring the use of "lead-free" plumbing for contructed after this date would not legally contain lead solder.  For Community Water Systems (CWS), it is single family structure that contains lead pipes or copper pipes with lead solder and/or is served by lead service lines installed after 1982.  For Non-Transient Non-Community Systems (NTNCWS), it is buildings that contain copper pipes with lead solder installed after 1982 and/or served by lead service lines.  For CWS, it is a building or multiple-family residences that contain lead pipes or copper pipes with lead solder installed after 1982, and/or is served by lead service lines.  For NTNCWS, it is buildings that contain copper pipes with lead solder installed before 1983.  Applies to CWS Only. Single family structures that contain	# of Sites  # of Sites  # of Sites  # of Sites	

# TEXAS COMMISSION ON ENVIRONMENTAL QUALITY LEAD/COPPER SAMPLE SITE POOL SELECTION FORM

<u>LEAC</u>	D/COPPER SAMP	LE SITE POOL SEI	ECTION FORM	
PW:	S NUMBER:			
			e as many pages as you	
I CE (A Jame	Tier 1, 2, 3, Other	(R)egular sample sites or (B)ack-up site	Type of Plumbing Material	Date of Construction
1				
2				
3				
4				
5				
6				
7				
8				
9				
10				
11				
12				
13				
14				
15				
16				
17				
18				
19				
20				
I have verified and certify that all site targeted Tier 1, 2, 3, or "other" san specifically represent areas of the sys	nple sites. Sampl	le sites selected are	e representative of the	distribution system and
Signature:		Date:		

Title:

TCEQ-20467 (Rev 02-22-16)

Printed Name:



## TEXAS COMMISSION ON ENVIRONMENTAL QUALITY INSTRUCTIONS FOR SELECTING LEAD/COPPER SAMPLING SITES

The objective when selecting sampling sites is to choose sites with interior plumbing materials of lead and/or copper, if possible. These types of sites are categorized on the <u>Lead/Copper Sample Site Selection Form</u> (SSF) from highest to lowest risk (#1-Other) based on their likelihood to leach lead and/or copper into the drinking water.

Identify a sample pool consisting of sites that fit in the highest category (ies) as possible (closest to #1). For example, search first for sites that meet the description in Categories #1 or #2 on the Form. If you can't find sites that fit in either of these categories, then try to find sites that fit in Categories #3. If you can't find any sites that fit in Categories #1-3, then all of your sampling sites will go in Category Other.

You must list the type of plumbing material and the date of construction for each site you put in Category #4.

Your Sampling Pool should include all identified sites EQUAL to the number of sites your system is required to sample during standard or initial monitoring. This is true for all systems on initial or reduced monitoring.

### **Example: Selecting Tier Sites and Sampling Pool**

- A PWS serves 3,301 to 10,000 people and is on reduced monitoring
- It is required to have a pre-approved sampling pool of 40 sites of which to sample from
- If your sampling pool needs updating, please use the site selection form and materials evaluation survey form to help identify the 40 sites. Turn it into TCEQ for approval.
- Identify which sites are "normal" sites and which sites are "reserved for back-up" sites
- Your Monitoring Plan will be updated at the same time your sampling pool is updated keep a copy in your records.
- Your normal tap water sampling is 20 sites on reduced monitoring. Make sure in advance that your customers want to participate.
- Bottles arrive and sampling begins.

Number of Sampling Sites Required for Standard / Initial Monitoring				
System Size	System Population	Number of PBCU sample sites		
Large	>100K	100		
	50,001 – 100K	60		
Medium	10,000 – 50K	60		
	3,301 – 10,000	40		
Small	501 – 3,300	20		
	101 -500	10		
	< 100	5		

#### Number of Sampling Sites Required for Routine / Reduced Monitoring System Size System Population Number of PBCU sample sites Large >100K 50 50,001 - 100K 30 10.000 - 50K 30 Medium 3,301 - 10,000 20 501 – 3,300 10 Small 101 -500 5 < 100 5

# TEXAS COMMISSION ON ENVIRONMENTAL QUALITY INSTRUCTIONS FOR SELECTING LEAD/COPPER SAMPLING SITES

### ADDITIONAL GUIDELINES WHEN SAMPLING TAP WATER MONITORING

- 1. When a sufficient number of Tier 1 sites do not exist or are inaccessible, you must complete your sample pool with Tier 2 sites.
- 2. For CWSs, when a sufficient number of Tier 1 and Tier 2 sites do not exist or are inaccessible, you must complete your sampling pool with Tier 3 sites.
- 3. Any water system that cannot complete its sampling at sites that meet the applicable tier criteria must complete sampling at representative sites throughout the distribution system.
- 4. You are not required to target buildings with lead solder installed after the 1988 Texas Lead ban.
- 5. You should not monitor at sampling sites that have water softeners; however, if all of your available sampling sites have water softeners, you should identify the highest risk sites (Tier 1) and monitor at those locations kitchen or bathroom sinks.
- 6. If you are not able to draw at least half of your samples from taps served by lead service lines, you must collect a sample from each available site that is serviced by a lead service line.
- 7. If you have lead service lines, but you have lead goosenecks or pigtails, you can collect tap water samples at the sites with the goosenecks and/or pigtails.
- 8. You should not sample at sites with point of use devices or point of entry devices.
- 9. Once monitoring begins, you must use the same sites, unless a site is no longer accessible to you or no longer fits the requirements of a priority site. If your sites have changes you must update your sampling pool.

## TEXAS COMMISSION ON ENVIRONMENTAL QUALITY LEAD/COPPER SAMPLING SITE MATERIALS EVALUATION SURVEY

The following is a checklist of resources for water systems to use when evaluating and identifying plumbing materials in their systems. Investigate the interior plumbing of your customers or your facility to determine what types of plumbing materials are present in your system. **Mark the resource(s) you used in your investigation in the blank(s) provided.** If you use a resource which is not listed below, indicate that in the blanks provided next to "Other Sources".

### **MATERIALS SURVEY CHECKLIST**

1.	<b>Distribution System Materials</b> - Sources available to determine the number of lead service lines or lead goosenecks in the distribution system.
	Distribution System Maps and Record Drawings (provide) Capital improvement plans for distribution system development. Utility records including meter installation records, customer complaint investigations and all historical documentation which indicate and/or confirm the location of lead service connections. Interview senior personnel. Perform community survey.
2.	<b>Interior Plumbing Materials</b> - Sources available to determine the number of residential or non-residential buildings which have interior lead pipe or copper pipe with lead solder joints.
	County appraisal district records. Contacts within the water system, municipal office or other local officials. Survey area plumbers about when and where copper pipe with lead solder was used. Interview residents - letters, phone survey, personal contact, etc. Interview local contractors, developers and builders.
3.	Corrosivity Characteristics - Public water supply systems shall identify whether the following construction materials are present in their distribution system and report to the State:  Lead from piping, solder, caulking, interior lining of distribution mains, alloys and home plumbing Copper from piping and alloys, service lines, and home plumbing.  Galvanized piping, service lines, and home plumbing.  Ferrous piping materials such as cast iron and steel
Other S	Sources (explain)
	Deturn the form to:

Return the form to:

TEXAS COMMISSION ON ENVIRONMENTAL QUALITY
PUBLIC DRINKING WATER – LEAD/COPPER PROGRAM - MC 155
P.O. BOX 13087
AUSTIN, TEXAS 78711-3087

If you have any questions, please call the Lead/Copper Program at Phone: 512/239-4691. Fax: 512/239-6050